

DATA SHEET – Fuel Regular H

Date: 15-05-2022

Parameter	Unit	Test Method	Typical Values
Colour			Black
Density 15°C	kg/m ³	ISO 12185	890 - 930
Flashpoint PM	°C	ISO 2719	> 61
Viscosity 40°C	mm ² /s	ISO 3104	30 – 60
Sulfur	wt.%	ISO 8754	≤ 1.0
Chlorine	wt.%	DIN 51 477-4	≤ 0.15
Ash	wt.%	ISO 6245	0.5 – 1.5
Sediments	wt.%	ISO 3734	≤ 2
Water	wt.%	ISO 3733	≤ 5
Calorific Value	MJ/kg	DIN 51 900	≥ 39.5
PCB	mg/kg	DS/EN 12 766-1,2	< 3 (not detected)

AVISTA OIL Danmark A/S

Juelsmindevej 6/18 ♦ DK-4400 Kalundborg ♦ Telefon +45 5956 5644 ♦ CVR 1016 9291 ♦ www.avista-oil.dk ♦ avista@avista-oil.dk
 Danske Andelskassers Bank A/S: Reg.nr.: 5951 ♦ Kontonr.: 4026976 ♦ IBAN DK5959510004026976 ♦ SWIFT: DANBDK22