



Product Data Sheet

01.08.2014

AVISTA OIL
Danmark A/S

AVISTA Fuel Regular H

Page 1 von 1

Parameter	Unit	Test Method	Typical Values
Colour			Black
Density 15°C	kg/m ³	EN ISO 12185	890 - 930
Flashpoint PM	°C	EN ISO 2719	> 61
Viscosity 40°C	mm ² /s	EN ISO 3104	30 – 60
Sulfur	wt. %	EN ISO 8754	≤ 1.0
Chlorine	wt. %	DIN 51 477-4	≤ 0.15
Ash	wt. %	EN ISO 6245	0.5 – 1.5
Sediments	wt. %	MRD SOP 039	≤ 2
Water	wt. %	ISO 3733	≤ 5
Calorific Value	MJ/kg	DIN 51 900	≥ 39.5
PCB	mg/kg	EN 12 766-1,2	< LOQ (< 5.0)*

* limit of quantitation

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

Contact:**AVISTA OIL Danmark A/S**

Juelsmindevej 6 – 18, 4400 Kalundborg, Dänemark

Telefon +45 59 56 56 44

Fax +45 59 56 56 88