



Product Data Sheet

11.12.2014

AVISTA OIL
Danmark A/S

AVISTA Fuel Regular LE

Page 1 von 1

Parameter	Unit	Test Method	Typical Values
Colour		ISO 2049	4 - 7
Density 15°C	kg/m ³	EN ISO 12185	800 - 815
Viscosity 20°C	mm ² /s	EN ISO 3104	0.9 – 2.0
Sulfur	wt. %	EN ISO 8754	0.3 – 1.5
Chlorine	wt. %	ASTM D 808	0.1 – 0.5
Pour Point	°C	ISO 3016	-39
Water	wt. %	ISO 6296	< 0.2
Calorific Value	MJ/kg	DIN 51 900	42

Distillation		ISO 3405	
Initial Boiling Point	°C		60
10 % v/v	°C		118
20 % v/v	°C		134
30 % v/v	°C		148
40 % v/v	°C		158
50 % v/v	°C		170
60 % v/v	°C		180
70 % v/v	°C		190
80 % v/v	°C		202
90 % v/v	°C		230
Final Boiling Point	°C		257

Contact:

AVISTA OIL Danmark A/S

Juelsmindevej 6 – 18, 4400 Kalundborg, Dänemark

Telefon +45 59 56 56 44

Fax +45 59 56 56 88