



Product Data Sheet

01.08.2014

AVISTA OIL
Danmark A/S

AVISTA Premium BF 15

Page 1 von 1

Parameter	Unit	Test Method	Typical Values
Colour		ISO 2049	< 4
Acid Number	mg KOH/g	ASTM D 974	< 1,5
Density 15°C	kg/m ³	EN ISO 12185	850 - 865
Flashpoint PMCC	°C	EN ISO 2719	> 100
Viscosity 20°C	mm ² /s	DIN 51 562 -1	35 – 45
Viscosity 40°C	mm ² /s	EN ISO 3104	14 – 20
Sulfur	wt. %	EN ISO 8754	< 0.4
Chlorine	mg/kg	DIN 51 408 -1	< 150
Pour Point	°C	ISO 3016	-12
Ash	wt. %	EN ISO 6245	< 0.01
PCB	mg/kg	DIN EN 12 766 – 1,2	< LOQ (< 5.0)*
Water Content	mg/kg	ASTM D 1744	< 300
Calorific Value	MJ/kg	DIN 51 900	> 42

* limit of quantitation

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

Contact:

AVISTA OIL Danmark A/S

Juelsmindevej 6 – 18, 4400 Kalundborg, Dänemark

Telefon +45 59 56 56 44

Fax +45 59 56 56 88