



Product Data Sheet

01.08.2014

AVISTA OIL
Danmark A/S

AVISTA B 250

Page 1 von 2

Parameter	Unit	Test Method	Typical Values
Density 15°C	kg/m ³	DIN 51757	910 - 960
Viscosity 100°C	mPas	DIN 53018	250 - 800
Flashpoint COC	°C	ISO 2592	> 250
Ash	wt. %	EN ISO 6245	2.0 - 6.0
Sulfur	wt. %	EN ISO 8754	0.8 - 1.3
Chlorine	wt. %	XRF	0.05 - 0.08
Nitrogen	wt. %	Kjeldahl	0.2 - 0.4
Phosphorus	wt. %	XRF	0.1 - 0.3
Cadmium	mg/kg	XRF	< 0.5
Calcium	wt. %	XRF	0.3 - 0.7
Chromium	wt. %	XRF	0.001 - 0.005
Copper	wt. %	XRF	0.005 - 0.015
Iron	wt. %	XRF	0.03 - 0.08
Lead	wt. %	XRF	< 0.15
Magnesium	wt. %	XRF	0.05 - 0.1
Mercury	mg/kg	XRF	< 1
Nickel	mg/kg	XRF	< 20
Silicon	wt. %	XRF	0.02 - 0.05
Thalium	mg/kg	XRF	< 10
Vanadium	mg/kg	XRF	< 10
Zinc	wt. %	XRF	0.1 - 0.4

Contact:

AVISTA OIL Danmark A/S

Juelsmindevej 6 – 18, 4400 Kalundborg, Dänemark

Telefon +45 59 56 56 44

Fax +45 59 56 56 88



Product Data Sheet

01.08.2014

AVISTA OIL
Danmark A/S

AVISTA B 250

Page 2 von 2

Contact:

AVISTA OIL Danmark A/S

Juelsmindevej 6 – 18, 4400 Kalundborg, Dänemark

Telefon +45 59 56 56 44

Fax

+45 59 56 56 88